

D400-IP-Camera-Specifications		
	Model	D400
Video	Image Sensor	1/3" CMOS Sensor
	Effective Pixels	2560x1440 (4.0 Megapixels)
	Lens	f=4.0mm Fixed, F=2.0
	Angle of View	Horizontal: 80°, Vertical: 42°
	Day/Night Mode	Auto Switchover
	Min. Illumination	0 Lux (With IR Illuminator)
	IR Distance	30 meters (LED: 18pcs/14mil/850nm)
	Backlight Compensation	Support
	Noise Reduction	3D DNR
	Compression	H.264
	Resolution	Main Stream: 2560x1440, 1080P, 720P; Sub Stream: 640x360
	Bitrate	Main Stream: 1024Kbps~6144Kbps, Sub Stream: 64Kbps~512Kbps
Frame Rate	Main Stream@30fps, Sub Stream@7fps	
Audio	Interface	Built-in Microphone
Network	Interface	One 10M/100Mbps RJ45
	Network Protocol	SSL, TCP/IP, UDP, UPNP, NTP, DHCP, DNS, DDNS
General	Power Supply	DC12V & PoE (IEEE 802.3af)
	Power Consumption	< 8W
	Working Environment	-10°C~+55°C (14°F~131°F), 10%~90%
	Ingress Protection	IP66
	Dimensions	Φ120*77mm
	Weight	480g
Warranty	Limited Warranty	2-Year Limited Warranty. For Support, Visit https://support.reolink.com/hc/en-us/ .