

Camera	Model	RLC-410 (4MP Version)
	Image Sensor	1/3" CMOS Sensor
	Effective Pixels	2560x1440 (4.0 Megapixels)
	Lens	f=4.0 mm Fixed, F=2.0
	Angle of View	Horizontal: 80°, Vertical: 42°
	Day/Night Mode	Auto Switchover
	Min. Illumination	0 Lux (With IR Illuminator)
	IR Distance	30 Meters (100ft)
	Backlight Compensation	Support
Noise Reduction	3D DNR	
Video	Compression	H.264
	Resolution	Mainstream: 2560x1440, 2048x1536, 2304x1296, 1080p, 720p; Substream: 640x360
	Bitrate	Mainstream: 1024Kbps~8192Kbps; Substream: 64Kbps~512Kbps
	Frame Rate	PAL: Mainstream@25fps, Substream@12fps; NTSC: Mainstream@30fps, Substream@15fps
Audio	Interface	Built-in Microphone
Network	Interface	One 10M/100Mbps RJ45
	Network Protocol	HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, FTP, ONVIF, P2P
	Browser Supported	IE, Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Max. User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams).
General	Power Supply	12V DC or 48V PoE (802.3af)
	Power Consumption	<8W
	Working Environment	-10°C~+55°C (14°F~131°F), Humidity: 10%~90%
	Ingress Protection	IP66
	Dimension	Φ65x188 mm
	Weight	450 g