

RLC-410W-4MP-IP-Camera-Specifications

	Model	RLC-410W (4MP Version)
Camera	Image Sensor	1/2.7" CMOS Sensor
	Effective Pixels	2560 x 1440 (4.0Megapixel)
	Lens	f=4.0mm F=2.0
	Angle of View	Horizontal: 80°, Vertical: 42°
	Day/Night Mode	Auto Switchover
	Min. Illumination	0 Lux (With IR Illuminator)
	IR Distance	30 Meters (LED: 18pcs/14mil/850nm)
	Backlight Compensation	Support
Video	Noise Reduction	3D DNR
	Compression	H.264
	Resolution	Main Stream: 2560x1440, 2048x1536, 2304x1296; Sub Stream: 640x480
	Bitrate	Main Stream: 1024Kbps ~ 8192Kbps, Sub Stream: 64Kbps ~ 512Kbps
Audio	Frame Rate	Main Stream@15fps, Sub Stream@6fps
	Interface	Built-in Microphone
Network	Interface	One 10M/100Mbps RJ45
	Network Protocol	HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Browser Supported	IE, Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smart Phone: iOS, Android
	Max. User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
	Storage	Micro SD socket, support motion detect record
WiFi	Wireless Standard	IEEE 802.11a/b/g/n
	Operating Frequency	2.4GHz / 5GHz
	Wireless Security	WPA-PSK/WPA2-PSK
General	Power Supply	DC12V
	Power Consumption	<8W
	Working Environment	-10°C ~ +55°C (14°F ~ 131°F), 10%~90%
	Ingress Protection	IP66
	Dimensions	Φ67 x 186mm
	Weight	425g