

|                |                           |                                                                                        |
|----------------|---------------------------|----------------------------------------------------------------------------------------|
|                | <b>Model</b>              | RLC-410WS                                                                              |
| <b>Camera</b>  | <b>Image Sensor</b>       | 1/3" CMOS Sensor                                                                       |
|                | <b>Effective Pixels</b>   | 2560 x 1440 (4.0 Megapixel)                                                            |
|                | <b>Lens</b>               | f=4.0mm Fixed, F=2.0                                                                   |
|                | <b>Angle of View</b>      | Horizontal: 80° , Vertical: 42°                                                        |
|                | <b>Day/Night Mode</b>     | Auto Switchover                                                                        |
|                | <b>Min. Illumination</b>  | 0 Lux (with IR Illuminator)                                                            |
|                | <b>IR Distance</b>        | 30 Meters                                                                              |
|                | <b>Backlight</b>          | Support                                                                                |
|                | <b>Noise Reduction</b>    | 3D DNR                                                                                 |
| <b>Video</b>   | <b>Compression</b>        | H.264                                                                                  |
|                | <b>Resolution</b>         | Main Stream: 2560 x 1440, 2048 x 1536, 2304 x 1296, 1080P, 720P; Sub Stream: 640 x 360 |
|                | <b>Bitrate</b>            | Main Stream: 1024Kbps ~ 8192Kbps, Sub Stream: 64Kbps ~ 512Kbps                         |
|                | <b>Frame Rate</b>         | PAL: Main Stream@25fps, Sub Stream@12fps; NTSC: Main Stream@30fps, Sub Stream@15fps    |
| <b>Audio</b>   | <b>Compression</b>        | AAC                                                                                    |
|                | <b>Interface</b>          | Built-in Microphone                                                                    |
| <b>Network</b> | <b>Interface</b>          | One 10M/100Mbps RJ45                                                                   |
|                | <b>Network Protocol</b>   | HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, FTP, ONVIF, P2P       |
|                | <b>Browser Supported</b>  | IE, Edge, Chrome, Firefox, Safari                                                      |
|                | <b>OS Supported</b>       | PC: Windows, Mac OS; Smart Phone: iOS, Android                                         |
|                | <b>Max. User Access</b>   | 20 Users                                                                               |
| <b>WiFi</b>    | <b>Storage</b>            | Embedded in 16GByte Micro SD Card, support motion detect record                        |
|                | <b>Wireless Standard</b>  | IEEE 802.11a/b/g/n                                                                     |
|                | <b>Operating</b>          | 2.4GHz / 5GHz                                                                          |
|                | <b>Wireless Security</b>  | WPA-PSK/WPA2-PSK                                                                       |
| <b>General</b> | <b>Power Supply</b>       | DC12V                                                                                  |
|                | <b>Power Consumption</b>  | <8W                                                                                    |
|                | <b>Working</b>            | -10°C~+55°C(14°F~131°F), 10%~90%                                                       |
|                | <b>Ingress Protection</b> | IP66                                                                                   |
|                | <b>Dimensions</b>         | Φ65 x188mm                                                                             |
|                | <b>Weight</b>             | 450g                                                                                   |