

Model	Model	RLC-423
Camera	Image Sensor	1/3" CMOS Sensor
	Effective Pixels	2560 x 1440 (4.0 Megapixel)
	Lens	f=2.8-12mm Auto-focus, F=1.4
	Angle of View	Horizontal: 35° ~ 95°, Vertical: 20° ~ 50°
	Day/Night Mode	Auto Switchover
	Min. Illumination	0 Lux (With IR Illuminator)
	IR Distance	60 Meters
	Backlight	Support
	Noise Reduction	3D DNR
Pan&Tilt	Pan&Tilt Range	Pan: 360°, Tilt: 0° ~ 90°
	Pan Speed	2.5° - 180°/s (Speed can be set)
	Tilt Speed	1.5° - 90°/s (Speed can be set)
	Preset	64
	Patrol	1 patrols, up to 16 presets per patrol
	Power Memory	Support
Video	Compression	H.264
	Resolution	Main Stream: 2560 x 1440, 2048 x 1536, 2304 x 1296, 1080P, 720P; Sub Stream: 640 x 360
	Bitrate	Main Stream: 1024Kbps ~ 8192Kbps, Sub Stream: 64Kbps ~ 512Kbps
	Frame Rate	PAL: Main Stream@25fps, Sub Stream@12fps; NTSC: Main Stream@30fps, Sub Stream@15fps
Network	Interface	One 10M/100Mbps RJ45
	Network Protocol	HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, FTP, ONVIF, P2P
	Browser Supported	IE, Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smart Phone: iOS, Android
	Max. User Access	20 Users
General	Power Supply	12V DC or 48V POE (802.3at).
	Power Consumption	<20W
	Working	-10℃~+55℃ (14°F~131°F), 10%~90%
	Ingress Protection	IP66
	Dimensions	Φ136 x 201mm
	Weight	1.70kg