RLK8-410B2D2-NVR-Kit-RLC-410-Specifications

Camera	**Model**	**RLC-410 (5MP/4MP Version)**
	Image Sensor	1/2.7" CMOS Sensor (5MP); 1/3" CMOS Sensor (4MP)
	Effective Pixels	2560 x 1920 (5.0 Megapixels); 2560x1440 (4.0 Megapixels)
	Lens	f=4.0mm F=2.0
	Angle of View	Horizontal: 80°, Vertical: 58° (5MP); Vertical: 42° (4MP)
	Day/Night Mode	Auto Switchover
	Min. Illumination	0 Lux (With IR Illuminator)
	IR Distance	30 Meters (100ft) (LED: 18pcs/14mil/850nm)
	Backlight Compensation	Support
	Noise Reduction	3D DNR
Video	Compression	H.264
	Resolution	5MP: Main Stream: 2560x1920, 2560x1440, 2048x1536, 2304x1296; Sub Stream: 640 x 480
		4MP: Mainstream: 2560x1440, 2048x1536, 2304x1296, 1080p, 720p; Substream: 640x360
	Bitrate	Main Stream: 1024Kbps ~ 8192Kbps, Sub Stream: 64Kbps ~ 512Kbps
	Frame Rate	5MP: Main Stream@25fps, Sub Stream@6fps
		4MP: PAL: Mainstream@25fps, Substream@12fps; NTSC: Mainstream@30fps, Substream@15fps
Audio	Interface	Built-in Microphone
Network	Interface	One 10M/100Mbps RJ45
	Network Protocol	HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Browser Supported	IE, Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smart Phone: iOS, Android
	Max. User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams).
	Storage	Built-in Micro SD socket, support motion detect record
General	Power Supply	DC12V & PoE (IEEE 802.3af)
	Power Consumption	<10W (5MP); <8W (4MP)
	Working Environment	-10℃~+55℃(14°F~131°F), 10%~90%
	Ingress Protection	IP66
	Dimensions	Φ67 x 186mm (5MP); Φ65x188 mm (4MP)
	Weight	350g (5MP); 450g (4MP)