

RLN16-410 PoE NVR Specifications		
<b>System</b>	GUI	16-Bit True Color
	Operating System	Embedded Linux OS
	Max. User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams).
<b>A/V Input</b>	Video Input	PoE IP Camera x 16
	Audio Input	Cameras with Built-in Mic
<b>A/V Output</b>	Decoding Resolution	5MP/4MP/3MP/1080p/720p
	VGA Output	1024*768, 1280*720, 1280*800, 1280*1024, 1440*900, 1920*1080p (1080p)
	HDMI Output	1024*768, 1280*720, 1280*800, 1280*1024, 1440*900, 1920*1080p (1080p)
	Audio Output	1CH RCA (Linear, 1kΩ)
	Playback Resolution	5MP/4MP/3MP/1080p/720p
	Synchronous Playback	4CH
<b>HDD</b>	SATA Devices	1 x 3TB (2 SATA Slots)
	Maximum Capacity	12TB (Maximum 4TB HDD/Port)
	External HDD	1 x e-Sata
<b>External Interface</b>	USB Connector	2 x USB 2.0
	Network Interface	RJ45, 10M/100M Ethernet, 16 Network Ports for IP Cameras, 1 Giga Network Port for LAN/WAN
<b>Network</b>	Network Protocol	HTTP, HTTPS, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Mobile Device	iPhone, Android Smartphones
	System Upgrade	Supports USB Update + Client Update
	Remote Software	Reolink App, IE Browser, Reolink Client (Windows/Mac)
<b>General</b>	Power Supply	Input 100~240V, 48V 2.5A
	Consumption	<20W Without PoE Cameras
	Working Temperature	-10°C~+55°C (14°F~131°F)
	Working Humidity	10%~90%
	Dimension (mm)	330(W) x 45(H) x 260(D)
	Weight (w/o HDD/DVD±RW)	3.0 kg