

	Model	Reolink Argus 2
Hardware Features	Image Sensor	SONY 1/2.8" CMOS Sensor (Starlight Sensor)
	Display Resolution	1920 x 1080 (2.0 Megapixel)
	Lens	Fixed, with IR CUT
	Angle of View	Diagonal: 130°
	PIR Detecting Distance	Up to 9 Meters
	PIR Detecting Angle	Horizontal: 120°
	Minimum Illumination	0 Lux (With IR Illuminator)
	IR Distance	Up to 33 Feet
	Dimensions	119 x 65 x 59mm
	Weight (battery included)	350g
	Interface	Built-in Micro SD Socket Built-in Microphone and Speaker Reset Button Micro USB Battery Charge Interface
Software Features	Protocols & Standards	SSL, TCP/IP, UDP, SMTP, DHCP, DNS, P2P
	Image Compression	H.264
	Maximal Frame Rate	15fps
	Code rate	768Kbps ~ 2048Kbps
	Audio	Two-Way Audio
	Browser Supported	Not Available; Access to Camera only on Reolink App on Mobie Phone Currently
	OS Supported	Smart Phone: iOS, Android
	Standby Awaken	PIR Alarm, Remote Access, Reset Button
Record Mode	PIR Alarm Record	
WiFi	Wireless Standard	IEEE 802.11b/g/n
	Operating Frequency	2.4GHz
	Wireless Security	WEP/WPA-PSK/WPA2-PSK
Battery	Type Specification	SAMSUNG/18650/5200mAh/3.63V, rechargeable Lithium Battery
	Battery Level Indication	Yes
	Ordinary Life	4 - 6 Months
Other Parameters	Temperature	Operating Temperature : -10°C~+55°C Storage Temperature: -40°C ~ 70°C
	Humidity	Operating Humidity: 20% ~ 85% Storage Humidity: 10% ~ 90%
	Weatherproof	Yes